

Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Hand-held grease guns

TUBI System's hand-held grease guns for industrial purposes come in lever-type, pneumatic and battery-operated versions.



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17 Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Manual grease guns

Manual grease guns are manufactured with the user and product lifetime in focus – we do not compromise on materials or manufacturing techniques. Choose from traditional lever-type, gun models and one or two-handed operated models.



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

TUBI 1 – Two-handed grease gun, classic

Two-handed grease gun – classic, with 450 mm hose and 4-jaw nozzle.

Technical specifications

Cartridges: For 400 g and 500 g cartridges.

Working pressure: 500 bar.

Max working pressure: 700+ bar.

Capacity: Approx. 1 cm³/stroke 400 bar back pressure.

Grease: Grease up to penetration class NLGI 3 can be used.

Thread: Connection thread hose female G1/8

Weight, approx: 1.4 kg excl. grease

Article number, grease gun only: 1959-01

Article number complete with 450 mm hose and 4-jaw nozzle: 1959-011





Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

TUBI 2 – One-handed grease gun, classic

One-handed grease gun – **classic**, with 450 mm hose and 4-jaw nozzle.

Consistent high pressure until the tube is empty, even in severely cold conditions. One-handed grip enables 40% faster lubrication. Unique design makes the lubrication easier. Does not need to be aired.

Technical specifications

Cartridges: For 400 g and 500 g cartridges.

Working pressure: 500 bar

Max working pressure: 700+ bar

Capacity: Approx. 1 cm³/stroke at 400 bar back pressure

Grease: Grease up to penetration class NLGI 3 can be used

Thread: Connection thread hose female G1/8

Weight: 1.4 kg excl. grease

Article number, grease gun only: 1994-02

Article number complete with 450 mm hose and 4-jaw nozzle: 1994-021





Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

TUBI 3 – One-handed grease gun, LS screw-in cartridge

One-handed grease gun – **for LS screw-in cartridge**, with 450 mm hose and 4-jaw nozzle.

The cartridge is screwed tight into the gun so that you can work without mess. The spring at the base of the nozzle helps to increase the capacity. One-handed grip enables 40% faster lubrication. Unique design makes the lubrication easier. Does not need to be aired. Consistent high pressure until the tube is empty, even in severely cold conditions.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Working pressure: 500 bar.

Max working pressure: 700+ bar.

Capacity: Approx. 1 cm³/stroke 400 bar back pressure.

Grease: Grease up to penetration class NLGI 2 can be used.

Thread: Connection thread hose female G1/8

Weight: 1.2 kg excl. grease

Article number, grease gun only: 2009-03

Article number complete with 450 mm hose and 4-jaw nozzle: 2009-031





Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Pneumatic grease guns

Pneumatic grease gun models suit all types of lubrication scenarios – quick and precise lubrication without the need for manual power. They are easy to use and work with very small compressors – the obvious choice for workshops when lubrication needs to be be fast



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Pneumatic TUBI grease gun – classic

Pneumatic TUBI grease gun – classic, with 450 mm hose and 4-jaw nozzle.

The grease gun supplies a constant amount of grease as long as the trigger is pressed.

Technical specifications

Cartridges: For 400 g and 500 g cartridges.

Working pressure: Max 400 bar

Capacity: Approx. 0.8 cm³/stroke, max 250 g/min

Recommended air pressure: 6 bar

Max air pressure: 8 bar

Air consumption: up to 120 I/min

Grease: Grease up to penetration class NLGI 3 can be used

Thread: Connection thread adapter hose female G1/8

Weight: 2.2 kg excl. grease

Article number, grease gun only: 1959-03

Article number complete with 700 mm hose and 4-jaw nozzle. 1959-031-700





Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Pneumatic TUBI grease guns – LS screw-in cartridge

Pneumatic TUBI grease gun for LS screw-in cartridge, with 700 mm hose and 4-jaw nozzle.

The grease gun supplies a constant amount of grease as long as the trigger is pressed. The spring at the base helps to increase the capacity.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Working pressure: max 400 bar

Recommended air pressure: 6 bar. Max air pressure: 8 bar

Air consumption: up to 120 I/min

Grease: Grease up to penetration class NLGI 2 can be used

Thread: Connection thread hose female G1/8

Weight: 2.0 kg excl. grease

Article number complete with 700 mm hose and **4-jaw nozzle.** 1162-LS





Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Battery-operated grease guns

Battery-operated grease guns are suitable for all types of lubrication. Combine the power of battery-operated guns with the freedom of not needing cords and hoses.



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Battery-operated TUBI Lincoln 12V grease gun – LS screw-in cartridge

Battery-operated 12V grease gun for **LS screw-in cartridge**, with 760 mm hose and 4-jaw nozzle. Also comes in classic TUBI model for regular grease cartridges.

It supplies a constant amount of grease as long as the trigger is depressed. Built-in LED lighting and indicator for battery level. Supplied in a practical case with 1 or 2 batteries, 12 Volt 1500 mAh Li-lon and fast-charger for 220V.

The cartridge is screwed tight into the gun so that you can work without mess. The spring at the base of the nozzle helps to increase the capacity.

Technical specifications

Cartridges: For 400 g LS screw-in cartridges

Working pressure: Max 550 bar

Grease: Grease up to penetration class NLGI 2 can be used

Connection thread hose: UNEF 7/16-28 (Adapter for G1/8" included)

Connection thread nozzle: NPT 1/8"

Charging time: Approx. 1 hour

Weight: 2.75 kg excl. grease

Article number	Description	No. batteries
1262-E-KL	Grease gun for regular DIN1284 cartridges	1







Contact

E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Orders & quotations

E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

1262-E-LS	Grease gun for LS screw-in cartridges	1
1264-E-KL	Grease gun for regular DIN1284 cartridges	2
1264-E-LS	Grease gun for LS screw-in cartridges	2
1261	Extra 12V Li-Ion battery	
1870-E	Extra battery charger 220V	
1875A	Battery charger for 12-24V vehicle plugs	



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

Battery-operated TUBI Lincoln 20V grease gun – LS screw-in cartridge

Battery-operated 20V grease gun for **LS screw-in cartridge**, with 900mm hose and 4-jaw nozzle. Also comes in classic TUBI model for regular grease cartridges.

The grease gun has high/low speed settings, a built-in working light, an integrated digital grease meter and a digital battery level indicator that is shown in the multi-function LCD display. It supplies a constant amount of grease as long as the trigger is activated. Supplied in a practical bag with 1 or 2 batteries, 20 Volt 2500 mAh Li-lon and fast-charger for 220V.

The cartridge is screwed tight into the gun so that you can work without mess. The spring at the base helps to increase the capacity.

Technical specifications

Cartridges: For 400 g LS screw-in cartridges

Working pressure: Max 690 bar

Grease: Grease up to penetration class NLGI 2 can be used

Connection thread hose: UNEF 7/16-28 (Adapter for G1/8" included)

Connection thread nozzle: NPT 1/8"

Charging time: Approx. 1 hour

Weight: 3.0 kg excl. grease

Article number	Description	No. batteries
1882-E-KL	Grease gun for regular DIN1284	1







Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

	cartridges	
1882-E-LS	Grease gun for LS screw-in cartridges	1
1884-E-KL	Grease gun for regular DIN1284 cartridges	2
1884-E-KL-PRVR	Same but with a pressure gauge and release valve.	2
1884-E-LS	Grease gun for LS screw-in cartridges	2
1871	Extra 20V 2,5Ah Li-Ion battery	
1872	Extra 20V 4,0Ah Li-Ion battery	
1870-E	Extra battery charger 220V	
1875A	Battery charger for 12-24V vehicle plugs	
2014-LISLA	Hose adapter UNEF7/16"-G1/8"	



Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17 Orders & quotations E-mail: order@tubisystem.se Web: www.tubisystem.se/reseller

Battery-operated TUBI grease gun 18V – LS screw-in cartridge

PRODUCT IS DISCONTINUED -Battery-operated TUBI grease gun 18V for **LS screw-in cartridge**, with 1000 mm hose and 4-jaw nozzle. Also comes in classic TUBI model for regular grease cartridges.

The cartridge is screwed tight into the gun so that you can work without mess. The spring at the base of the nozzle helps to increase the capacity. The grease gun supplies a constant amount of grease as long as the trigger is pressed.

Supplied in a practical bag. Two batteries, 18.0V 1500 mAh and fast-charger included.

Technical specifications

Cartridges: For 400 g LS screw-in cartridges

Working pressure: Max 690 bar

Capacity: Approx.100 g/min depending on the grease quality and temperature.

Working capacity: Approx. 2.0 kg grease on a fully-charged battery

Grease: Grease up to penetration class NLGI 2 can be used

Connection thread hose: G1/8

Charging time approx 1 hour

Weight: 3.5 kg excl. grease

Article number	Description
2009-200	Grease gun for regular







Contact E-mail: info@tubisystem.se Phone: +46 63 12 07 17

	DIN1284 cartridges
2009-230	Grease gun for LS screw-in cartridges
2009-18NIMH	Extra 18V NiMH battery
2009-NAT	Extra battery charger 220V
2009-CIGG	Battery charger for 12V vehicle plugs