

Pumps

Pumps for bulk handling of lubricants. TUBI System's range of pumps work with the most common containers on the market (18 kg to 180 kg). We have selected the best pumps on the market to ensure operational reliability and functionality.

RAASM Grease pump 50:1 for 16-25kg

Pneumatic grease pump, pressure ratio 50:1. Suitable for grease up to NLGI 2. Connects to the drum lid with lid bung adapter 800-30.

Length of suction pipe 480 mm adapted to 16 - 25 kg drums.

Technical data

Pressure ratio: 50:1

Max air use: 230 NL/min

Capacity at 8 bar (NLGI 2): 1500 g/min

Connection thread air female: G1/4"

Connection thread grease female: G3/8"

Pump tube Ø: 30 mm

Suction pipe, length: 480 mm

For drum size: 16 - 25 kg

Lid bung adapter: Not included

Article number: 62048



Grease filler pump for Central lubrication system

Hand-operated grease pump for refilling of central lubrication systems, 16-20 kg.

Hose with agricultural standard quick connector, with check valve and adapter with male G1/4" included. For use with grease type NLGI 00-2. Bucket not included.



Technical data

Capacity per stroke: 50 g

Hose length: 1.5 m

Hose Ø: 3/4"

Pump tube Ø: 40 mm

Lid suits Ø: 285 - 330 mm

Pump tube length: 545 mm

Quick connector (male): G1/8"

For packaging: 16 - 20 kg

Handle: No

Follower plate included: No

Article number: CP16F

Pneumatic Grease filler pump for central lubrication system

Pneumatic grease filler pump for central lubrication systems, 16-20 kg, including FRL unit for lubrication, filtering and setting of air-pressure.

Pump pressure ratio of 50:1 with adjustable pressure reduction from 100 down to 5 bar, for refilling of central lubrication systems and chain lubrication systems in forest machinery. Provides a full 1500 gram/min free flow. Outlet hose of 2m 1/2", complete with ball valve and quick connector with check valve and adapter with male G1/4" included. Pump tube Ø 30 mm. For grease type NLGI 000-2. Follower plate included.



Technical data

Pressure ratio: 50:1

Capacity per stroke: 1500 g/min

Hose length: 2.0 m

Hose Ø: 1/2"

Pump tube Ø: 30 mm

Lid suits Ø: 285 - 330 mm

Adapter male: G1/4"

For drum size: 16 - 25 kg

Handle: Yes

Follower plate included: Yes

TUBI 2-in-1 Grease filler pump for Central lubrication system



TUBI Grease filler pump for Central lubrication system, 400 g LS screw-in cartridge or regular cartridge. Unit for refilling of central lubrication units from a grease cartridge. Simple handling, no need to carry buckets and so on.

Insert your grease cartridge of choice and use the lever to push the grease into the central lubrication container. Supplied for use with LS screw-in cartridges and can be easily re-built to be used with regular standard DIN1284 grease cartridges. 20 mm cylindrical connection between the filler and the adapter. Supplement with a straight or 90° adapter which is mounted on the central lubrication unit. The adapter comes in M20 x 1.5 (Beka Max and others) or M22 x 1.5 (Lincoln etc) to suit the most common units.

Models and article numbers

Article number	Description
2017-ALFP-2IN1	Grease filler pump 2-in-1
2017-ALFP	Grease filler pump for DIN1284 cartridges only
2017-M20	Adapter M20
2017-M20-90	Adapter 90° M20
2017-M22	Adapter M22
2017-M22-90	Adapter 90° M22

