TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Accessories and spare parts for grease guns

Hoses, nozzles and extra equipment for all our different grease guns and systems. You will also find all the spare parts for our products here.

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Accessories for grease guns

Choose from a full range of special nozzles, hoses, mounting fixtures and other tools to make your job easier.

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI Lockable Grease nozzle G1/8"



The nozzle can be locked in place and opened with very little effort, even under the highest pressure. It has 4 hardened jaws in spring steel, an integrated check valve, a unique locking mechanism that is easy to remove even under back pressure of up to 1000 bar. In independent tests it has withstood pressure of up to 2000 bar without leakage.

Technical specifications

Diameter front section: 16 mm

Length: 74 mm

Working pressure: 690 bar

Burst pressure: 1030 bar

Connection thread: G1/8"

Weight: just 85 gram

Article number
TM34

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI High pressure hose R1/8"



Easy-to-use high pressure hose made of thermoplastic polymer with polyester reinforcement.

Comes with and without spring for extra breakage protection.

Technical specifications

Working pressure: 400bar

Burst pressure: 1000bar

Standard: DIN1283

Connection thread: R1/8"

Article number	Length
T300	300 mm
T450	450 mm
T500	500 mm
T600	600 mm
T700	700 mm
T700-SPR	700 mm with spring
T800	800 mm
T900	900 mm
T1000	1000 mm
T1000-SPR	1000 mm with spring

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

T2000	2000 mm

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI RetroFit adapter pipe – LS screw-in cartridge



TUBI's LS system makes lubrication possible even in extreme conditions. The spring helps to push the grease through, even during the coldest of Nordic climates. The lid protects the cartridge from shocks, knocks and also from dirt.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.65 kg excl. grease

Article number	Suitable for
2005-033	Tubi 18V, Techway, IR, and others
2005-053	Pressol
2013-043	Alemite , Milwaukee 18V
2013-053	China model 12, 18V
2013-063	Speedy grease old, with steel tube
2014-073	Lincoln, Dewalt, Makita and others
2014-083	Hallbauer, and others
2016-093	SKF/Lincoln 20V
2016-103	Pneumatic grease gun with pivotable handle

2017-113	Speedy grease new, with plastic tube
2020-123	Mato
2020-133	Makita P-90451
2020-143	Pressol 20V
2021-163	Makita DGP180

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI RetroFit adapter pipe – standard cartridge



TUBI's LS system makes lubrication possible even in extreme conditions. The spring helps to push the grease through, even during the coldest of Nordic climates. The lid protects the cartridge from shocks, knocks and also from dirt.

Technical specifications

Cartridges: For 400 g DIN1284 standard cartridges

Weight: 0.65 kg excl. grease

Article number	Suitable for
2005-03	Tubi 18V, Techway, IR, and others
2005-05	Pressol
2013-04	Alemite , Milwaukee 18V
2013-05	China model 12, 18V
2013-06	Speedy grease old, with steel tube
2014-07	Lincoln, Dewalt, Makita and others
2014-08	Hallbauer, and others
2016-09	SKF/Lincoln 20V
2016-10	Pneumatic grease gun with pivotable handle

2017-11	Speedy grease new, with plastic tube
2020-12	Mato
2020-13	Makita P-90451
2020-14	Pressol 20V
2021-16	Makita DGP180

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Smörjmunstycke Standard Rc1/8"



Hydrauliskt munstycke med 4 st lösa härdade backar. Följer med i våra kompletta smörjsprutor.

Tekniska specifikationer

Diameter: 15mm

Längd: 38mm

Arbetstryck: 400bar

Sprängtryck: 1000bar

Anslutningsgänga: Rc1/8"

Artikelnummer
TM11

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI LS refiller 3-way, with valve for G1/2” hose



Refill adapter for LS screw-in cartridges, mounted on bucket/drum pumps with M20x1 connection thread. Hose stud for 1/2” hose. The valve regulates the flow to the cartridge.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease

Article number	
5050-06VX3-M20	3-way with valve

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI LS refiller 3-way, with valve for G1/4” connection



Refill adapter for LS screw-in cartridges, mounted on buckets/drum pumps with G1/4" connection thread. The valve regulates the flow to the cartridge.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease

Article number	
5050-04VX3	3-way with valve

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI LS refiller straight for M20x1



Refill adapter for LS screw-in cartridges, mounted on bucket/drum pumps with M20x1 connection thread.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease


Article number	
5050-M20	straight

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI Lockable hose pack UNEF7/16"



The nozzle can be locked in place and opened with very little effort, even under the highest pressure. It has 4 hardened jaws in spring steel, an integrated check valve, a unique locking mechanism that is easy to remove even under back pressure of up to 1000 bar. In independent tests it has withstood pressure of up to 2000 bar without leakage.

Easy-to-use high pressure hose made of thermoplastic polymer with polyester reinforcement and break protection. **Hose adapter** suitable for many American brands, such as Lincoln, Dewalt and Alemite.

Technical specifications

Nozzle TM34

Diameter front section: 16 mm

Length: 74 mm

Working pressure: 690 bar

Burst pressure: 1030 bar

Connection thread: G1/8"

Weight: just 85 gram

Hose T1000 SPR

Length: 1000 mm

Burst pressure: 1000 bar

Break protection: 2 springs

Connection thread: G1/8"

Adapter 2014-LISLA

Material: Steal, alloy zinc

Connection thread: f G1/8", m UNEF7/16"

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Article number
2018-LISLA

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Spare parts for grease guns

Full range of spare parts for all of TUBI System's hand-held models. Everything from complete pump parts to the smallest screw or label.

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Red seal

Red cartridge seal for grease cartridges that do not have built-in seals.

For more information, see the manual that comes with your TUBI grease gun.

Article number: P-RED



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Grey seal

Grey cartridge seal for European grease cartridges that do not have built-in seals.

For more information, see the manual that comes with your TUBI grease gun..

Article number: P-GREY



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

White seal ring

WHITE seal for sealing the ends of standard cartridges, used in TUBI 1 and TUBI 2.

Article number: P-WHITE



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Black seal

Black seal for bulk grease. The seal allows you to use the entire cartridge tube as a grease container.

Article number: P-BLACK



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Hose holder with steel adapter.

Hose holder for easy connection of the hose to your TUBI grease gun.

Connect the hose using the accompanying adapter and fix it in place with a suitable thread locker. To simplify removal, apply heat to loosen up the factory-applied thread locker.

Article number: TT03

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Ancillary equipment for grease guns

Accessories for all of TUBI's hand-held grease guns. Choose from flow meters, pressure gauges or valves. All hand-held models can be combined with any fixtures to find a solution that suits the specific application to be addressed.

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI Pressure relief valve – manometer and grease return.



Pressure relief valve with grease return and manometer.

The return hose returns surplus grease back in to the gun for simple, clean removal of the nozzle.

Manometer for reading the current pressure, graded from 0 - 1000 bar.

Mounted on the TUBI System on any TUBI grease gun, stated upon order.

Technical specifications

Working pressure: 500 bar.

Max working pressure: 700+ bar.

Grease: Grease up to penetration class NLGI 3 can be used.

Connection: Connection thread hose female G1/8”.


Article number	Grease gun connection
2009-PRVR	G1/8"
2009-PRVR-7-16	UNEF 7/16"

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

TUBI Pressure relief valve – with grease return



Pressure relief valve that returns surplus grease.

The return hose returns surplus grease back in to the gun for simple, clean removal of the nozzle.

Mounted on the TUBI System on any TUBI grease gun, stated upon order.

Technical specifications

Working pressure: 500 bar.

Max working pressure: 700+ bar.

Grease: Grease up to penetration class NLGI 3 can be used.

Connection: Connection thread hose female G1/8".

Article number: 2009-PRVR-1337

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Digital grease meter



Grease meter for measuring the quantity of grease. For use with pneumatic lubrication equipment and lever-type pumps.

The grease meter can also be installed into the system. Through the unique oval gear mechanism construction, you can easily see the amount discharged through the meter. The meter is equipped with an LCD display that indicates the delivered quantity in grams (resettable through the reset button) as well as the total volume in kg. Four 8mm high digits on the working display and four 4mm high digits on the total amount. Working temperature max +60° C. Two 1.5V (AAA) batteries are needed to power the meter, estimated to last approx. 10,000 hours under normal usage. Dimensions: Ø 60 mm, length 65 mm.

Technical specifications

Max pressure: 500 bar

Min burst pressure: 1000 bar

Connection thread in-flow (f): G1/8"

Connection thread out-flow (f): G1/8"

Max working temperature: +60° C

Accuracy +/- at NLGI000-2: 0.03

Flow area: 0-1000 g/min

Weight: 0.5 kg

Article number: PF-100

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Manometer 1000 bar

Manometer in stainless material, glycerine filled with a downward connection thread.

Technical specifications

Ø Manometer: 63 mm

Scale: 0 - 1000 bar

Connection thread: G1/4" (f)

Article number: MM-1000

TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Manometer 600 bar

Manometer in stainless material, glycerine filled with a downward connection thread.

Technical specifications

Ø Manometer: 63 mm

Scale: 0 - 600 bar

Connection thread: G1/4" (f)

Article number: MM-600