

Accessories for grease guns

Choose from a full range of special nozzles, hoses, mounting fixtures and other tools to make your job easier.

TUBI Lockable Grease nozzle G1/8"

The nozzle can be locked in place and opened with very little effort, even under the highest pressure. It has 4 hardened jaws in spring steel, an integrated check valve, a unique locking mechanism that is easy to remove even under back pressure of up to 1000 bar. In independent tests it has withstood pressure of up to 2000 bar without leakage.



Technical specifications

Diameter front section: 16 mm

Length: 74 mm

Working pressure: 690 bar

Burst pressure: 1030 bar

Connection thread: G1/8"

Weight: just 85 gram

Article number
TM34

TUBI High pressure hose R1/8"



Easy-to-use high pressure hose made of thermoplastic polymer with polyester reinforcement.

Comes with and without spring for extra breakage protection.

Technical specifications

Working pressure: 400bar

Burst pressure: 1000bar

Standard: DIN1283

Connection thread: R1/8"

Article number	Length
T300	300 mm
T450	450 mm
T500	500 mm
T600	600 mm
T700	700 mm
T700-SPR	700 mm with spring
T800	800 mm
T900	900 mm
T1000	1000 mm
T1000-SPR	1000 mm with spring



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

T2000

2000 mm

TUBI RetroFit adapter pipe - LS screw-in cartridge

TUBI's LS system makes lubrication possible even in extreme conditions. The spring helps to push the grease through, even during the coldest of Nordic climates. The lid protects the cartridge from shocks, knocks and also from dirt.



Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.65 kg excl. grease

Article number	Suitable for
2005-033	Tubi 18V, Techway, IR, and others
2005-053	Pressol
2013-043	Alemite , Milwaukee 18V
2013-053	China model 12, 18V
2013-063	Speedy grease old, with steel tube
2014-073	Lincoln, Dewalt, Makita and others
2014-083	Hallbauer, and others
2016-093	SKF/Lincoln 20V
2016-103	Pneumatic grease gun with pivotable handle

2017-113	Speedy grease new, with plastic tube
2020-123	Mato
2020-133	Makita P-90451
2020-143	Pressol 20V
2021-163	Makita DGP180

TUBI RetroFit adapter pipe – standard cartridge

TUBI's LS system makes lubrication possible even in extreme conditions. The spring helps to push the grease through, even during the coldest of Nordic climates. The lid protects the cartridge from shocks, knocks and also from dirt.



Technical specifications

Cartridges: For 400 g DIN1284 standard cartridges

Weight: 0.65 kg excl. grease

Article number	Suitable for
2005-03	Tubi 18V, Techway, IR, and others
2005-05	Pressol
2013-04	Alemite , Milwaukee 18V
2013-05	China model 12, 18V
2013-06	Speedy grease old, with steel tube
2014-07	Lincoln, Dewalt, Makita and others
2014-08	Hallbauer, and others
2016-09	SKF/Lincoln 20V
2016-10	Pneumatic grease gun with pivotable handle

2017-11	Speedy grease new, with plastic tube
2020-12	Mato
2020-13	Makita P-90451
2020-14	Pressol 20V
2021-16	Makita DGP180

Smörjmunstycke Standard Rc1/8"

Hydrauliskt munstycke med 4 st lösa
härdade backar. Följer med i våra kompletta
smörjsprutor.



Tekniska specifikationer

Diameter: 15mm

Längd: 38mm

Arbetsstryck: 400bar

Sprängtryck: 1000bar

Anslutningsgänga: Rc1/8"

Artikelnummer
TM11

TUBI LS refiller 3-way, with valve for G1/2" hose

Refill adapter for LS screw-in cartridges, mounted on bucket/drum pumps with M20x1 connection thread. Hose stud for 1/2" hose. The valve regulates the flow to the cartridge.



Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease

Article number	
5050-06VX3-M20	3-way with valve

TUBI LS refiller 3-way, with valve for G1/4"

Refill adapter for LS screw-in cartridges, mounted on buckets/drum pumps with G1/4" connection thread. The valve regulates the flow to the cartridge.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease



Article number	
5050-04VX3	3-way with valve

TUBI LS refiller straight for M20x1

Refill adapter for LS screw-in cartridges,
mounted on bucket/drum pumps with
M20x1 connection thread.

Technical specifications

Cartridges: For 400 g MLS screw-in cartridges

Weight: 0.75 kg excl. grease




Article number	
5050-M20	straight

TUBI Lockable hose pack UNEF7/16"

The nozzle can be locked in place and opened with very little effort, even under the highest pressure. It has 4 hardened jaws in spring steel, an integrated check valve, a unique locking mechanism that is easy to remove even under back pressure of up to 1000 bar. In independent tests it has withstood pressure of up to 2000 bar without leakage.

Easy-to-use high pressure hose made of thermoplastic polymer with polyester reinforcement and break protection. **Hose adapter** suitable for many American brands, such as Lincoln, Dewalt and Alemite.



Technical specifications

Nozzle TM34

Diameter front section: 16 mm

Length: 74 mm

Working pressure: 690 bar

Burst pressure: 1030 bar

Connection thread: G1/8"

Weight: just 85 gram

Hose T1000 SPR

Length: 1000 mm

Burst pressure: 1000 bar

Break protection: 2 springs

Connection thread: G1/8"

Adapter 2014-LISLA

Material: Steel, alloy zinc

Connection thread: f G1/8", m UNEF7/16"

Article number
2018-LISLA