


TUBI Lockable hose pack UNEF7/16"

The nozzle can be locked in place and opened with very little effort, even under the highest pressure. It has 4 hardened jaws in spring steel, an integrated check valve, a unique locking mechanism that is easy to remove even under back pressure of up to 1000 bar. In independent tests it has withstood pressure of up to 2000 bar without leakage.

Easy-to-use high pressure hose made of thermoplastic polymer with polyester reinforcement and break protection. **Hose adapter** suitable for many American brands, such as Lincoln, Dewalt and Alemite.



Technical specifications

Nozzle TM34

Diameter front section: 16 mm

Length: 74 mm

Working pressure: 690 bar

Burst pressure: 1030 bar

Connection thread: G1/8"

Weight: just 85 gram

Hose T1000 SPR

Length: 1000 mm

Burst pressure: 1000 bar

Break protection: 2 springs

Connection thread: G1/8"

Adapter 2014-LISLA

Material: Steel, alloy zinc

Connection thread: f G1/8", m UNEF7/16"



TUBI System AB
Org. no: 556279-7968
Web: www.tubisystem.se/en

Contact
E-mail: info@tubisystem.se
Phone: +46 63 12 07 17

Orders & quotations
E-mail: order@tubisystem.se
Web: www.tubisystem.se/reseller

Article number

2018-LISLA
